

# IMPACT-RATED INDOOR HOARDING

- No fixings required to anything
- No ground penetration
- Compliant to AS4687

## FREE-STANDING

Designed and structurally engineered to free-stand up to 8mH using a standard 90 x 45 MPG pine stud – no bracing or fixings required



## IMPACT-RATED

Pre-certified and impact tested from both the front and rear of the hoarding for compliance to AS4687

**INDOOR HOARDING 'WEIGHT TO HEIGHT' GUIDE FOR COMPLIANCE TO AS4687**

SOLID PANEL HEIGHT – MAX (H)	STUD – 90 X 45 (4X2) MPG10	QUANTITY OF COUNTER-WEIGHTS PER STACK	MAX INTERVAL BETWEEN COUNTER-WEIGHT STACKS	CEILING, FLOOR OR SIDE BRACING REQUIREMENTS
1.2m	90 x 45 MPG10	2	2.4mW	Freestanding - Not Required
1.8m	90 x 45 MPG10	3	1.2mW	Freestanding - Not Required
2.4m	90 x 45 MPG10	3	1.2mW	Freestanding - Not Required
3m	90 x 45 MPG10	4	1.2mW	Freestanding - Not Required
3.6m	90 x 45 MPG10	4	1.2mW	Freestanding - Not Required
4m	90 x 45 MPG10	5	1.2mW	Freestanding - Not Required
4.6m	90 x 45 MPG10	6	1.2mW	Freestanding - Not Required
5m	90 x 45 MPG10	8	1.2mW	Freestanding - Not Required
5.6m	90 x 45 MPG10	10	1.2mW	Freestanding - Not Required
6m	90 x 45 MPG10	12	1.2mW	Freestanding - Not Required
6.6m	90 x 45 MPG10	16	1.2mW	Freestanding - Not Required
7m	90 x 45 MPG10	16	1.2mW	Freestanding - Not Required
7.6m	90 x 45 MPG10	20	1.2mW	Freestanding - Not Required
8m	90 x 45 MPG10	20	1.2mW	Freestanding - Not Required

Lower Cross-Brace and Support Post Required for all Certification - See LOMAX for Technical Guide / Build Process



MODULAR HOARDING AND FENCING SOLUTIONS  
COMPACT | REUSABLE | FREESTANDING

For all enquiries, please contact:

1300 0 LOMAX  
1300 0 56629

lomaxsystem.com